



## OFF CENTER LOAD CELL TYPE SUP12

### APPLICATIONS:

Off centre load cell type SUP12 can be used in small capacity weighing systems.

Some applications are:

- Small weighing platforms
- Hopper weighing, etc.

### MAIN FEATURES:

- Universal use
- Low cost
- Aluminium construction
- Independent from centre of load application
- Platform size 300X350 mm



**NOMINAL LOAD:** kg 5-7-10-15-30-50

<b>SPECIFICATION ACCORDING TO VDI/VDE 2637</b>			
<b><u>METROLOGICAL CHARACTERISTICS</u></b>	<b>Par.</b>	<b>Un.</b>	
NOMINAL LOAD	Ln	Kg	5÷50
INITIAL LOAD	Lp	% Ln	20
MAXIMUM LOAD	Ll	% Ln	150
NON-LINEARITY	Flin	% Ln	0,02
HISTERESIS ERROR	Fu	% Ln	0,02
REPEATABILITY ERROR	Fv	% Ln	0,02
CREEP-30 MINUTES	Fcr	% Ln	0,03
NOMINAL TEMPERATURE RANGE	Btn	°C	-10+40
ZERO TEMPERATURE DRIFT (OVER 10 °C)	TK0	% Cn	0,025
OUTPUT TEMPERATURE DRIFT (OVER 10 °C)	TKC	% Cn	0,025
THERMAL GRADIENT		°K/h	<5
<b><u>ELECTRICAL DATA</u></b>			
NOMINAL OUTPUT	Cn	m V/V	2
NOMINAL OUTPUT TOLERANCE	Dc	±% Cn	10
NOMINAL SUPPLY VOLTAGE	Bsu	V	1÷10
MAXIMUM SUPPLY VOLTAGE	Usmax	V	15
INPUT RESISTANCE	Re	Ω	410±15%
OUTPUT RESISTANCE	Ra	Ω	350±3%
INSULATION RESISTANCE @ 20V	Ris	MΩ	>2000
ZERO OUTPUT TOLERANCE	Do	±% Cn	±2
<b><u>MECHANICAL DATA</u></b>			
BREAKING LOAD	Ld	% Ln	200
MAXIMUN SIDE LOAD	Llq	% Ln	100
DEFLECTION	hn	mm	<1
CABLE LENGTH		mm	3000
WEIGHT		Kg	0,2
<b><u>ENVIRONMENTAL CONDITIONS</u></b>			

### CELMi s.r.l.

Largo Brugnatelli 13/16 20090 BUCCINASCO (MI) ITALY

Tel: +39-0245712209 / 0257503712 Fax: +39-0245705836 / 0257506211

Internet: [www.celmi.com](http://www.celmi.com) mail: [info@celmi.com](mailto:info@celmi.com)